

Speed Queen®

On-Premises

Softmount Washer-Extractors

- 18 lb (8 kg) Washer-Extractor
- 25 lb (11 kg) Washer-Extractor
- 35 lb (16 kg) Washer-Extractor
- 55 lb (25 kg) Washer-Extractor
- 75 lb (34 kg) Washer-Extractor
- 100 lb (45 kg) Washer-Extractor
- 135 lb (61 kg) Washer-Extractor
- 165 lb (75 kg) Washer-Extractor



A Passion to Lead

OPL Softmount Washer-Extractors Specifications

	SX18	SX25	SX35	SX55	SX75	SX100	SX135	SX165
Capacity - lb (kg)	18 (8)	25 (11)	35 (16)	55 (25)	75 (34)	100 (45)	135 (61)	165 (75)
Width - in (mm)	26" (660)	26" (660)	30 13/16" (783)	35 7/16" (900)	41 13/16" (1060)	47 5/16" (1200)	47 5/16" (1200)	51 13/16" (1300)
Depth - in (mm)	30 3/4" (780)	34 5/16" (870)	37 13/16" (960)	40" (1016)	46" (1168)	52 7/16" (1330)	59 1/8" (1500)	63 7/8" (1620)
Height - in (mm)	40 5/8" (1031)	40 5/8" (1031)	47" (1194)	60 7/8" (1544)	61 7/16" (1560)	75 5/8" (1920)	75 5/8" (1920)	82 13/16" (2100)
Cylinder Diameter - in (mm)	20 15/16" (530)	20 15/16" (530)	25 5/8" (650)	29 1/2" (750)	33 1/2" (850)	38 5/8" (980)	38 5/8" (980)	43 1/8" (1095)
Cylinder Depth - in (mm)	13.5/8" (345)	17 5/16" (440)	19 3/4" (500)	20 15/16" (530)	21 1/8" (537)	23 1/2" (597)	30 1/2" (775)	30 1/2" (775)
Cylinder Volume - cu.ft (liter)	2.7 (76)	3.4 (97)	5.9 (167)	8.3 (234)	10.8 (305)	15.9 (451)	20.7 (585)	25.8 (730)
Door Opening Size - in (mm)	11 7/8" (300)	11 7/8" (300)	11 7/8" (300)	15 5/8" (395)	15 5/8" (395)	19 3/4" (500)	19 3/4" (500)	24 1/2" (622)
Door Bottom to Floor - in (mm)	11" (279)	11" (279)	15 5/8" (395)	22" (559)	22" (559)	25 1/2" (648)	25 1/2" (648)	28" (710)
Wash Speed (rpm)	10-50	10-50	10-50	10-50	10-50	10-50	10-50	10-50
Distribution Speed (rpm)	82	82	74	69	65	61	61	100
Extract Speed (rpm)	250-1000	250-1000	250-1000	250-1000	250-1000	250-800	250-800	250-750
Extract G-Force (rpm)	19-296	19-296	23-363	26-418	30-475	34-350	34-350	344
Water Inlet Conn. - in (mm)	3 x 3/4" (19)	3 x 3/4" (19)	3 x 3/4" (19)	3 x 3/4" (19)	3 x 3/4" (19)	4 x 3/4" (19)	4 x 3/4" (19)	4 x 1" (25)
Steam Inlet Conn. - in (mm)	3/8" (10)	3/8" (10)	3/8" (10)	3/8" (10)	3/8" (10)	1/2" (13)	1/2" (13)	3/4" (19)
Drain Connection Size - in (mm)	2" (51)	2" (51)	2" (51)	3" (76)	3" (76)	3" (76)	3" (76)	2 x 3" (76)
Motor Size - HP (kw)	1 (.75)	1 (.75)	2 (1.5)	4 (3)	5.4 (4)	7.4 (5.5)	10 (7.5)	15 (11.5)
Voltage/Hz/Phase Non-heat Circuit Breaker-FLA	200-240/50-60 1/3 15-10	200-240/50-60 1/3 15-10	200-240/50-60 1/3 15-12	200-240/50-60 1/3 20-16	200-240/50-60/3 N/A	200-240/50-60/3 N/A	200-240/50-60/3 N/A	200-240/50-60/3 N/A
Voltage/Hz/Phase Non-heat Circuit Breaker-FLA	200-240/50-60/3 N/A	200-240/50-60/3 N/A	200-240/50-60/3 N/A	200-240/50-60/3 N/A	200-240/50-60/3 20-15	200-240/50-60/3 20-17	200-240/50-60/3 30-20	200-240/50-60/3 40-32
Voltage/Hz/Phase* Elect. heat Circuit Breaker-FLA	200-240/50-60/3 30-28	200-240/50-60/3 30-29	200-240/50-60/3 60-58	200-240/50-60/3 60-58	200-240/50-60/3 60-58	200-240/50-60/3 90-88	200-240/50-60/3 90-88	N/A
Voltage/Hz/Phase* Non-heat Circuit Breaker-FLA	380-415/50-60/3 N/A	380-415/50-60/3 N/A	380-415/50-60/3 N/A	380-415/50-60/3 N/A	380-415/50-60/3 15-12	380-415/50-60/3 20-17	380-415/50-60/3 25-17	380-415/50-60/3 25-20
Voltage/Hz/Phase Elect. heat Circuit Breaker-FLA	380-415/50-60/3 20-17	380-415/50-60/3 20-18	380-415/50-60/3 40-36	380-415/50-60/3 40-36	380-415/50-60/3 40-36	380-415/50-60/3 60-55	380-415/50-60/3 60-55	N/A
Voltage/Hz/Phase* Non-heat Circuit Breaker-FLA	440-480/50-60/3 15-6***	440-480/50-60/3 15-6***	440-480/50-60/3 15-12***	440-480/50-60/3 15-12	440-480/50-60/3 15-12	440-480/50-60/3 20-17	440-480/50-60/3 25-17	440-480/50-60/3 25-20
Voltage/Hz/Phase* Elect. heat Circuit Breaker-FLA	440-480/50-60/3 25-20	440-480/50-60/3 25-21	440-480/50-60/3 50-41	440-480/50-60/3 50-41	440-480/50-60/3 50-41	440-480/50-60/3 70-62	440-480/50-60/3 70-62	440-480/50-60/3 N/A
Shipping Dimensions Approx. - in (mm)	Height 44 15/16" (1140) Width 28 7/8" (732) Depth 32 7/8" (832)	48 7/8" (1240) 28 7/8" (732) 37 7/16" (950)	51 11/16" (1310) 33 1/2" (850) 43 3/8" (1100)	65" (1650) 40 1/4" (1020) 45 3/8" (1150)	68 1/8" (1730) 45 3/4" (1160) 48 7/16" (1230)	79 1/8" (2010) 51 1/4" (1300) 56 3/8" (1430)	79 1/8" (2010) 51 1/4" (1300) 64 1/4" (1630)	90 11/16" (2300) 57 1/8" (1450) 67 7/8" (1720)
Net Weight - lb (kg)	520 (236)	531 (241)	765 (347)	1247 (570)	1907 (865)	3351 (1520)	3626 (1645)	4630 (2100)
Shipping Weight - lb (kg)	624 (283)	639.5 (290)	1030 (467)	1380 (630)	2194 (995)	3741 (1697)	4017 (1822)	5113 (2319)
Agency Approvals**	CE, cETL _{US}	CE, cETL _{US}	CE, cETL _{US}	CE, cETL _{US}	CE, cETL _{US}	CE, cETL _{US}	CE, cETL _{US}	CE, cETL _{US}

* Special order may require longer time, check with factory.

** Agency approvals may vary depending on configuration. Consult factory for details.

*** CE only.

Voltages above or below listed may require a buck-boost transfer.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

©Copyright 2009 Alliance Laundry Systems LLC